



Installation Record

Installation Type (e.g. Attic, Floor, Wall):	
R-Value (RSI):	
Installed Thickness:	Settled Thickness*:
Area Insulated (excluding openings):	
Bags Installed:	Bag Weight:

*Dry blown attic application only.

Installer Information

Name: _____
Address: _____
Date of Application: _____

Customer Information

Name: _____
Address: _____

Manufacturer's Warranty

Thermo-Cell Industries Ltd. warrants that Pro-Cell Green Insulation is manufactured to meet or exceed product standards CAN\ULC-S703-01 and ASTM C739-2000.

Pro-Cell Green Insulation is guaranteed to provide the thermal performance indicated above for the normal life of the building, provided the material is installed according to manufacturer's instructions. The liability of Thermo-Cell will be limited to the replacement of defective insulation or installation of additional insulation provided a copy of this completed card and proof of purchase is supplied to Thermo-Cell.

In no event shall Thermo-Cell be responsible or liable for any damages resulting from the use or misuse or installation of the product, whether such damage is direct, indirect, consequential or otherwise. This warranty excludes all damages to the insulation resulting from defects or deterioration in the structure, physical or mechanical abuse and or acts of nature.

THERMO-CELL INDUSTRIES LIMITED
An ISO 9001:2000 Certified Company

For more information visit our website at www.thermocell.com
Or contact us at
1-877-575-3600 Atlantic Canada
1-800-267-1433 Ontario, Quebec and Eastern United States

C.C.M.C. Listing # 08251

February 2007

WEATHERSHIELD COVERAGE CHARTS

ATTIC APPLICATION (25 lb/11.3 kg bag)									
Thermal Resistance		Blown Thickness		Minimum Thickness		Minimum Weight per Unit Area		Maximum Coverage per Bag	
RSI Value	R Value	mm	inches	mm	inches	Kg/m ²	lb/ft ²	m ²	ft ²
2.1	12	90	3.5	80	3.2	2.05	0.42	5.5	59.4
3.5	20	150	5.9	134	5.3	3.42	0.70	3.3	35.6
4.9	28	210	8.3	187	7.4	4.79	0.98	2.4	25.4
5.6	32	240	9.4	214	8.4	5.48	1.12	2.1	22.3
6.2	35	262	10.3	234	9.2	5.99	1.23	1.9	20.4
6.3	36	270	10.6	241	9.5	6.16	1.26	1.8	19.8
7.0	40	299	11.8	267	10.5	6.84	1.40	1.7	17.8
8.8	50	374	14.7	334	13.2	8.56	1.75	1.3	14.3
9.7	55	412	16.2	368	14.5	9.41	1.93	1.2	13.0
10.5	60	449	17.7	401	15.8	10.27	2.11	1.1	11.9

ENVIROSHIELD WALL APPLICATION (25 lb/11.3 kg bag)								
Thermal Resistance		Framing		Coverage per Bag			# of Bags Required	
RSI Value	R Value	mm	inches	m ²	ft ²	No of 8ft ² Cavities	100 m ²	1000 ft ²
2.3	12.8	38x89	2x4	3.0	32.3	3	33	31
3.6	20.2	38x140	2x6	1.9	20.8	2	52	48

February 2007